

# SPU PUMP MODELS

The High Head - Low Flow SPU Pumps



"A Trusted Partner in Pump Solutions"

## SPU-3

### SELF-PRIMING

- ▶ 850 rpm (2.3m) 7ft - 1150 rpm 2.9m (9ft)
- ▶ 1450 rpm (4.5m) 15ft - 1750 rpm 7.6m (25ft)
- ▶ 1950 rpm (7.6m) 25ft - 2150 rpm 7.6m (25ft)

### TECHNICAL DATA

- ▶ **Impeller Diameter:** 279.4 mm (11")
- ▶ **R.P.M.:** from 850 rpm to 2150 rpm
- ▶ **Max. Solids:** 20.63 mm (13/16")
- ▶ **Net Weight:** 214kg (472 lbs)
- ▶ **Shipping Weights:** 225kg (497 lbs)

\* Before using this table, check the NPSHr.

### SELF-PRIMING

- ▶ 850 rpm (2.4m) 8ft - 1150 rpm 3.0m (10ft)
- ▶ 1450 rpm (3.6m) 12ft - 1750 rpm 3.9m (13ft)
- ▶ 1950 rpm (4.5m) 15ft - 2150 rpm 5.2m (17ft)

### TECHNICAL DATA

- ▶ **Impeller Diameter:** 279.4 mm (11")
- ▶ **R.P.M.:** from 850 rpm to 2150 rpm
- ▶ **Max. Solids:** 28.57 mm (1.1/8")
- ▶ **Net Weight:** 272kg (600 lbs)
- ▶ **Shipping Weights:** 297kg (655 lbs)

## SPU-4

\* Before using this table, check the NPSHr.

## SPU-6

### SELF-PRIMING

- ▶ 850 rpm (2.4m) 8ft - 1150 rpm 3.0m (10ft)
- ▶ 1450 rpm (4.2m) 10ft - 1750 rpm 4.5m (15ft)
- ▶ 1950 rpm (4.5m) 15ft

### TECHNICAL DATA

- ▶ **Impeller Diameter:** 317.5 mm (12.1/2")
- ▶ **R.P.M.:** from 850 rpm to 1950 rpm
- ▶ **Max. Solids:** 31.75 mm (1.1/4")
- ▶ **Net Weight:** 413kg (910 lbs)
- ▶ **Shipping Weights:** 437kg (965 lbs)

\* Before using this table, check the NPSHr.

## SELF-PRIMING TRASH PUMPS

### SPT/SPU SERIES

## SPT PUMP



SPU PUMP



### AREAS OF APPLICATION

- Water and Waste Treatment
- Effluent Treatment
- Municipality, City Water
- Sewage Lift Station
- Sugar Industries
- Industrial Chemical Waste



"A Trusted Partner in Pump Solutions"

1320 Britannia Road East  
Mississauga, Ontario, Canada. L4W 1C8

Phone: (905) 461-9617 | Fax: (905) 461-9618  
Toll Free: 1-866-217-PUMP (7867)  
Email: sales@rotechpumps.com | www.rotechpumps.com

bestow.in

# SPT PUMP MODELS

The High Flow - Low Head SPT Pumps

Rotech Pump presents a revolutionary range of Self-Priming Centrifugal Trash Pumps. Ergonomically designed and aesthetically perfect, these pumps are economical & offer trouble-free operation in handling solids laden liquids and slurries. Pump features a large volume design which allows them to re-prime automatically in a completely open system without the need of suction or discharge check valves. And this is workable with the pump only partially filled with liquid and completely dry suction line. Pump can handle up to 75mm spherical solids, depending on pump models. In case that pump shaft or bearings need service or repair, the entire rotating assembly can be removed without disturbing pump casing or pipelines. Rotating assembly is sealed with an O-Ring, allowing for external adjustments of clearance.

## SPT-2

### SELF-PRIMING

- ▶ 1150 rpm (7.3m) 24ft - 1450 rpm 7.6m (25ft)
- ▶ 1750 rpm (7.6m) 25ft - 2050 rpm 7.6m (25ft)
- ▶ 2350 rpm (7.6m) 25ft - 2650 rpm 7.6m (25ft)
- ▶ 2650 rpm (7.6m) 25ft - 2900 rpm 7.6m (25ft)

### TECHNICAL DATA

- ▶ **Impeller Diameter:** 158.75 mm (6.1/4")
- ▶ **R.P.M.:** from 1150 rpm to 2900 rpm
- ▶ **Max. Solids:** 44.45 mm (1.3/4")
- ▶ **Net Weight:** 92kg (203 lbs)
- ▶ **Shipping Weights:** 114kg (252 lbs)

\* Before using this table, check the NPSHr.

### SELF-PRIMING

- ▶ 650 rpm (1.5m) 5ft - 750 rpm 1.8m (6ft)
- ▶ 850 rpm (2.4m) 8ft - 950 rpm 3.0m (10ft)
- ▶ 1050 rpm (4.0m) 13ft - 1150 rpm 4.9m (16ft)
- ▶ 1250 rpm (5.5m) 18ft - 1350 rpm 5.8m (19ft)
- ▶ 1450 rpm (6.4m) 21ft - 1550 rpm 6.4m (21ft)
- ▶ 1650 rpm (6.7m) 22ft - 1750 rpm 6.7m (22ft)
- ▶ 1850 rpm (7.6m) 25ft - 1950 rpm 7.6m (25ft)

- ▶ 2050 rpm (7.6m) 25ft - 2150 rpm 7.6m (25ft)

### TECHNICAL DATA

- ▶ **Impeller Diameter:** 222.25 mm (8.3/4")
- ▶ **R.P.M.:** from 650 rpm to 2150 rpm
- ▶ **Max. Solids:** 63.5 mm (2.1/2")
- ▶ **Net Weight:** 183kg (404 lbs)
- ▶ **Shipping Weights:** 205kg (452 lbs)

\* Before using this table, check the NPSHr.

## SPT-3

## SPT-4

### SELF-PRIMING

- ▶ 650 rpm (1.5m) 5ft - 750 rpm 2.4m (8ft)
- ▶ 850 rpm (4.9m) 16ft - 950 rpm 5.8m (19ft)
- ▶ 1050 rpm (6.7m) 22ft - 1150 rpm 7.3m (24ft)
- ▶ 1250 rpm (7.6m) 25ft - 1350 rpm 7.6m (25ft)
- ▶ 1450 rpm (7.6m) 25ft - 1550 rpm 7.6m (25ft)
- ▶ 1650 rpm (7.6m) 25ft - 1750 rpm 7.6m (25ft)
- ▶ 1850 rpm (7.6m) 25ft - 1950 rpm 7.6m (25ft)

### TECHNICAL DATA

- ▶ **Impeller Diameter:** 247.65 mm (9.3/4")
- ▶ **R.P.M.:** from 650 rpm to 1950 rpm
- ▶ **Max. Solids:** 76.2 mm (3")
- ▶ **Net Weight:** 259.5kg (600 lbs)
- ▶ **Shipping Weights:** 280kg (655 lbs)

\* Before using this table, check the NPSHr.

## SPT-6

### SELF-PRIMING

- ▶ 650 rpm (2.4m) 5ft - 750 rpm 2.7m (9ft)
- ▶ 850 rpm (3.6m) 12ft - 950 rpm 4.2m (14ft)
- ▶ 1050 rpm (5.5m) 18ft - 1150 rpm 6.4m (21ft)
- ▶ 1250 rpm (6.4m) 21ft - 1350 rpm 6.7m (22ft)
- ▶ 1450 rpm (7.0m) 23ft - 1550 rpm 7.6m (25ft)

### TECHNICAL DATA

- ▶ **Impeller Diameter:** 314.32 mm (12.3/8")
- ▶ **R.P.M.:** from 650 rpm to 1550 rpm
- ▶ **Max. Solids:** 76.2 mm (3")
- ▶ **Net Weight:** 364 (802 lbs)
- ▶ **Shipping Weights:** 391kg (862 lbs)

\* Before using this table, check the NPSHr.

### SELF-PRIMING

- ▶ 650 rpm (2.7m) 9ft - 750 rpm 3.7m (12ft)
- ▶ 850 rpm (4.6m) 15ft - 950 rpm 5.2m (17ft)
- ▶ 1050 rpm (6.1m) 20ft - 1150 rpm 6.4m (21ft)
- ▶ 1250 rpm (6.7m) 22ft - 1350 rpm 7.0m (23ft)

### TECHNICAL DATA

- ▶ **Impeller Diameter:** 374.65 mm (14.3/4")
- ▶ **R.P.M.:** from 650 rpm to 1350 rpm
- ▶ **Max. Solids:** 76.2 mm (3")
- ▶ **Net Weight:** 581 (1295 lbs)
- ▶ **Shipping Weights:** 634kg (1399 lbs)

\* Before using this table, check the NPSHr.

## SPT-8

## SPT-10

### SELF-PRIMING

- ▶ 650 rpm (2.1m) 7ft - 750 rpm 3.4m (11ft)
- ▶ 850 rpm (4.3m) 14ft - 950 rpm 5.2m (17ft)
- ▶ 1050 rpm (5.5m) 18ft - 1150 rpm 5.5m (18ft)
- ▶ 1250 rpm (5.8m) 19ft - 1350 rpm 6.7m (22ft)
- ▶ 1450 rpm (6.7m) 22ft

### TECHNICAL DATA

- ▶ **Impeller Diameter:** 374.65 mm (14.3/4")
- ▶ **R.P.M.:** from 650 rpm to 1450 rpm
- ▶ **Max. Solids:** 76.2 mm (3")
- ▶ **Net Weight:** 635 (1400 lbs)
- ▶ **Shipping Weights:** 663kg (1461 lbs)

\* Before using this table, check the NPSHr.

### SELF-PRIMING

- ▶ 650 rpm (1.6m) 5ft - 750 rpm 2.7m (9ft)
- ▶ 850 rpm (3.9m) 13ft - 950 rpm 4.5m (15ft)
- ▶ 1050 rpm (4.9m) 16ft - 1150 rpm 4.9m (16ft)
- ▶ 1250 rpm (4.9m) 16ft

### TECHNICAL DATA

- ▶ **Impeller Diameter:** 457.2 mm (18")
- ▶ **R.P.M.:** from 650 rpm to 1250 rpm
- ▶ **Max. Solids:** 76.2 mm (3")
- ▶ **Net Weight:** 998kg (2200 lbs)
- ▶ **Shipping Weights:** 1066kg (2350 lbs)

\* Before using this table, check the NPSHr.

## SPT-12